

® TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p. Technical and Test Institute for Construction Prague, SOE

Akreditované laboratoře, Autorizovaná osoba, Notifikovaná osoba, Oznámený subjekt, Subjekt pro technické posuzování, Certifikační orgány, Inspekční orgán / Accredited Laboratories, Authorized Body, Notified Body, Technical Assessment Body, Certification Bodies, Inspection Body • Prosecká 811/76a, Prosek, 190 00 Praha 9, Czech Republic

Notified Body 1020

CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 1020 - CPR - 070045575

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Lighting columns of polymer composites reinforced with glass fibres and lighting columns with extension arms with base plate or rooted, intended for lights installation

version: with flange type SKPF, SKPF PP and SKPF LS rooted type SKPW and SKPW PP

in diameters of the base Ø 100÷250 mm and a height from 3,0 to 12,0 m

placed on the market under the name or trade mark of

NCT S.A.

Marklowicka street 30A, 44-300 Wodzisław Śląski, Poland, INo: PL6472213249

and produced in the manufacturing plant:

NCT S.A.

Marklowicka street 30A, 44-300 Wodzisław Śląski, Poland

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 40-7:2002

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 28 June 2013 under CPD and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The Annex No. 1 is a part of Certificate No. 1020 - CPR - 070045575.

The stamp of the Notified Body 1020

Ostrava, August 16, 2023



Dipl. Eng. Vojtěch Šebek Deputy manager of the Notified Body



® TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p. Technical and Test Institute for Construction Prague, SOE

Akreditované laboratoře, Autorizovaná osoba, Notifikovaná osoba, Oznámený subjekt, Subjekt pro technické posuzování, Certifikační orgány, Inspekční orgán / Accredited Laboratories, Authorized Body, Notified Body, Technical Assessment Body, Certification Bodies, Inspection Body • Prosecká 811/76a, Prosek, 190 00 Praha 9, Czech Republic

ANNEX No. 1 CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 1020 - CPR - 070045575

Lighting columns of polymer composites reinforced with glass fibres and lighting columns with extension arms with base plate or rooted, intended for lights installation

version: with flange type SKPF, SKPF PP and SKPF \(\Lambda \) rooted type SKPW and SKPW PP

in diameters of the base Ø 100÷250 mm and a height from 3,0 to 12,0 m

The requirements according to EN 12767 have functional properties with regard to passive safety in the event of an accident of vehicles classified according to the following table:

Lighting columns made of fiberglass-reinforced polymer composites with a boom	Classification by EN 12767	
	EN 12767:2007	EN 12767:2019
rooted type SKPW in base diameters (at the ground surface) ø193 mm and smaller and height of 9,0 m and lower ²⁾	70NE3	70-NE-B-S-SE-MD-0
rooted type SKPW in base diameters (at the ground surface) ø220 mm and smaller and height of 9,0 m and lower ²⁾	50NE3	50-NE-B-S-NS-MD-0
with flange type SKPF in base diameters (at the flange) ø193mm and smaller and height of 9,0 m and lower ²⁾	70NE2	70-NE-C-S-SE-MD-0
rooted type SKPW in base diameters (at the ground surface) ø220 mm and height 12,0 m	100LE3	100-LE-C-S-SE-MD-0
rooted type SKPW in base diameters (at the ground surface) ø220 mm and height 12,0 m with an anchoring plate 1)	100HE1	100-HE-E-S-SE-MD-0
rooted type SKPW PP in base diameters (at the ground surface) ø250mm and smaller and height of 12,0 m and lower ²⁾	100NE2 70NE2 50NE2	100-NE-C-S-SE-MD-0 70-NE-C-S-SE-MD-0 50-NE-C-S-SE-MD-0
with flange type SKPF PP in base diameters (at the flange) ø250mm and smaller and height of 12,0 m and lower ²⁾	100NE3 70NE3 50NE3	100-NE-B-S-SE-MD-0 70-NE-B-S-SE-MD-0 50-NE-B-S-SE-MD-0
Other columns covered by EN 40-7 certificate	Class 0	Class 0

¹⁾ According to the manufacturer's assessment

This Annex is an integral part of the Certificate of constancy of performance No.1020 - CPR - 070045575.

The stamp of the Notified Body 1020

Ostrava, August 16, 2023



Dipl. Eng. Vojtěch Šebek Deputy manager of the Notified Body

²⁾ The product line of columns with passive safety elements according to point G.2.1 of the EN 12767: 2019 standard